



Daphne Super Turbine Oil Series

High Performance Turbine Oil

Description

Daphne Super Turbine Oil is a super long life premium turbine oil formulated with highly refined hydrotreated paraffinic base oil incorporating various additives such as oxidation inhibitor, rust prevention additive, anti-foaming and oiliness agents.

Application

Specially formulated for use in turbo system such as large steam turbine, high-speed turbo compressor, turbo compressor for chlorine gas and nuclear power generator.

Characteristics

1. **Exceptional Oxidation Stability** - A combination of oxidation inhibitor and highly refined hydrotreated base oil assures excellent oxidation stability under severe operating condition.
2. **Anti-Chlorine Property** - Highly refined base oil with special additive formulation for anti-chlorine gas and chlorine acid.
3. **Low Sulphur Content** - The highly refined hydrotreated base oil which has extremely low sulphur content further improves oxidation stability and deterioration due to the forming of acids.
4. **Excellent Anti-Corrosion & Anti-Rust Properties** - Effective rust preventive agent and corrosion inhibitor prevent corrosion caused by water and acid produced through deterioration process.

Packing

20L pail, 200L drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Lubricant Product Information**Typical Specifications****Daphne Super Turbine Oil Series**

Available Grades	ASTM METHOD	<u>32-S</u>	<u>46-S</u>	<u>56-S</u>	<u>68-S</u>
Colour	D-1500	L0.5	L0.5	L0.5	L0.5
Density 15 °C g/cm ³	D-4052	0.8682	0.8707	0.8717	0.8729
Flash Point (COC) °C	D-92	234	238	228	242
Viscosity, cSt @ 40 °C	D-445	30.92	47.48	56.16	69.16
@ 100 °C		5.263	6.930	7.770	8.777
Viscosity Index	D-2270	101	101	102	101
Pour Point °C	D-6749	-15	-15	-15	-15
TAN (mgKOH/g)	D-974	0.08	0.09	0.09	0.09
Sulphated Ash wt%	D-874	<0.01	<0.01	<0.01	<0.01
Copper Corrosion (100°C x 3h)	D-130	1(1a)	1(1a)	1(1a)	1(1a)

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.