

Idemitsu ATF

Description

Idemitsu ATF is the latest technologically advanced automatic transmission fluid suitable for use in all modern AT units. This special formulation enhances smooth & positive shifting under severe working conditions.

Application

Recommended for all modern AT transmission gearbox from Asian auto makers (Especially Japanese cars) to American, Continental and South Korean cars.

Compatible with:

ATF DEXRON II E / 5D06 / 2384K / 3314 / 3317, ATF Fluid D-II / D-III / WS, ATF JWS 3317, Alumix Fluid ATF DII / DIII Multi / D3-SP, ATF Type T / T-II / T-III / T-IV, ATF M-III / M-V / FZ, Besco ATF II / III, Dia-Queen: ATF II / ATF AW / ATF-SPII / ATF SPII M / ATF J-2, DEXRON II-E, DEXRON III / VI / III-G, Diamond ATF SP-IIM / III, MERCON, Ultra ATF / ATF Z1 / ATF DW-1

Characteristics

1. Super long-life automatic transmission fluid.
2. Superior protection against premature wear & tear of moving parts.
3. Excellent protection and performance at high temperatures and high loads.

Packaging

24 x 1 Litre Carton, 20 Litres Pail, 200 Litres Drum

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Typical Specifications

Idemitsu ATF

	ASTM METHOD	
Color (Appearance)		Red
Density 15 °C g/cm ³	D-4052	0.8508
Flash Point (COC) °C	D-92	194
Viscosity, cSt @ 100 °C	D-445	7.316
BF Viscosity @ -40 °C	D-2983	16,800
Pour Point °C	D-97	-45
TBN,HClO ₄ (mgKOH/g)	D-2896	3.36
Foaming @ 93.5°C (ml)	D-892	0-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.