



Daphne Thermic Oil Series

High Performance Heat Transfer Oil

Description

Daphne Thermic Oil Series is a range of heat transfer oil formulated with highly refined hydrocracked paraffinic base oil with specially selected additives to provide exceptional oxidation and thermal stability, thus, minimizing viscosity changes and deposits forming at the heating surfaces.

Application

Recommended as a heat transfer oil for both open type and closed type heating systems. It is most suitable for long-term application. Recommended operating temperature range is up to 200°C in the open systems and 300°C in the closed systems.

Note: Heat transfer oil requirements are different in open and closed systems. There is a greater risk of oil oxidation in the open systems.

Characteristics

1. **Excellent Oxidation Stability** - A highly refined paraffinic base oil and anti-oxidation additives assure excellent oxidation stability and reduce problems caused by formation of sludge.
2. **Excellent Thermal Stability** - Addition of special additives assure excellent thermal stability minimizes viscosity changes
3. **High Viscosity Index**
4. **High Flash Point**

Packing

20L pail, 200L drum



Information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturer is not liable for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of performance against patent infringement.

Lubricant Product Information

Typical Specifications

Daphne Thermic Oil Series

Available Grades	ASTM METHOD	<u>32-S</u>	<u>68-S</u>
Colour	D-1500	L0.5	L0.5
Density 15 °C g/cm ³	D-4052	0.8630	0.8670
Flash Point (COC) °C	D-92	226	258
Pour Point °C	D-874	-20.0	-25.0
Viscosity, cSt @ 40 °C	D-445	31.27	68.00
@ 100 °C		5.365	9.260
Viscosity Index	D-2270	105	109
TAN (mgKOH/g)	D-974	0.08	0.08
Foam @ 24°C	D-892	<10-0	<10-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.