

idemitsu IFG5 5W-30 SP/GF-6A

Description

idemitsu IFG5 5W-30 SP/GF-6A is formulated by Quintet Guard technology that the perfect harmony of these five processes not only helps to protect the engine but also maximize performance. Fully Synthetic Motor Oil.

Application

For all gasoline engine requiring SAE 5W-30 including turbocharged gasoline direct injection and gasoline hybrid cars

Characteristics

- Piston cleanliness
- Stop & Go protection
- Reducing further wear growth even for high mileage vehicles
- Maximizing power
- Excellent Fuel Saving

Meets the performance level:

API SP / ILSAC GF-6A

Packing

1 liter & 20 liters

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Product Data Sheet

Typical Specifications

idemitsu IFG5 5W-30 SP/GF-6A

	ASTM METHOD	
SAE Viscosity grade		5W-30
Color (Appearance)	D-1500	L. Brown
Flash Point (COC) °C	D-92	228
Viscosity, cSt @ 40 °C	D-445	66.04
@ 100 °C	D-445	11.11
Pour Point °C	D-97	-40
Viscosity Index	D-2270	161
TBN, HClO ₄ (mgKOH/g)	D-2896	8.93
Sulfated Ash wt%	D-874	0.86
Noack Test 250 °C, 1Hr @ wt%	D5800	9.8 (Max-13.0 wt%)

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.