

## Description

DAPHNE SUPER COAT JP is an aerosol-type anti-rust lubrication oil used for rust prevention and lubrication for various machines, jigs and tools, and metal products.

## Features & Characteristics

- (1) Despite of its thin oil film, it has excellent water displacement, rust prevention and lubrication.
- (2) It can also be used on non-metals and prevents rust and discoloration.
- (3) It has excellent permeability, so it can be easily applied even in narrow areas. By setting a long nozzle, it is possible to apply it without waste.
- (4) It is effective in removing loose rust. After spraying, it penetrates into rust and floats it, so it can be easily removed with nylon or wire brush.
- (5) It is possible to use it upside down.
- (6) The residual gas inside the container can be vented using the attached cap. It is convenient and safe when disposing the empty can.
- (7) It does not contain barium-based compounds that may place a burden on the environment

## Performance

Test Item	Test Method	Unit	Result
Oil film thickness	Estimation	μm	1.7
Humidity chamber test(480Hr)	JISK2246	-	Rank A
Salt spray test life(48Hr)	ASTM B117	-	Rank A
Exposure test(720Hr)	-	-	Rank A
Water displacement	JISK2246	-	Passed

## Impact on non-ferrous metals

Copper,Aluminum,Zinc,Chromium etc. are no influence

## Impact on resins

Polystyrene,Polyethylene,Polycarbonate,Polyamide,ABS,Acrylic etc. are no influence

## Package

400 ml ×10 / case

## Attention

- (1) Do not use it for any purpose other than rust prevention and lubricant.
- (2) Do not use it for human body.
- (3) Do not use it near fire.
- (4) Do not store it in places exposed to direct sunlight or where the temperature exceeds 40 ° C.
- (5) Do not put in fire.
- (6) It may cause irritation if it comes into contact with the skin or enters the eyes. When using, wear protective gloves and glasses, and do not touch the skin or eyes directly.
- (7) Keep it out of reach of children.
- (8) Read the notes on the container carefully before use.

**Product  
introduction Video**



- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or via the internet.  
<https://www.idemitsu.com/jp/business/lube/>
- Due to continual product research and development, the information contained herein is subject to change without notification.

**Malaysia**  
**Idemitsu Lube (Malaysia) Sdn. Bhd.**

**Kuala Lumpur Branch**  
Tel: (60) 3 6157 9529 Fax: +60 3 6157 9636

**Johor Branch**  
Tel: (60) 7 550 0460 Fax: +60 7 550 0466

**Penang Branch**  
Tel: (60) 4 501 2268 Fax: +60 4 501 2269

**Singapore Branch**  
Tel: (65) 6256 6843 Fax: +65 6256 6384

**Thailand**  
**Apollo (Thailand) Co., Ltd**  
Tel: (66) 3 845 6900 Fax: (66) 3 821 0099

**Vietnam**  
**Idemitsu Lube Vietnam Co., Ltd.**  
Tel: (84) 31 3246 508 Fax: (84) 31 3246 509

**India**  
**Idemitsu Lube India Pvt. Ltd.**  
Tel: (91) 11 66794200 Fax: (91) 11 66794259

**Indonesia**  
**PT. Idemitsu Lube Techno Indonesia**  
**PT. Idemitsu Lube Indonesia**  
Tel:(62) 21 8997 7630

**Philippines**  
**Idemitsu Lubricants Philippines Inc.**  
Tel: (63) 2 8 282 855 Fax: (63) 2 8 524 0617