## **DAPHNE ALPHACOOL EW**





## **Description**

DAPHNE ALPHA COOL EW is a water soluble cutting fluid for aluminum alloy, steel, and alloy steel. Especially in the working of aluminum alloy, this product has excellent performance for form rolling tap, finishing reaming which is difficult to work with conventional products.

## Features & **Characteristics**

DAPHNE ALPHA COOL EW is a cutting fluid that is gave the measure against emulsion break. Special surfactants that IDEMITSU developed with original technology and other selected raw materials are included in this product. And these included materials prevent emulsion break and decay.

- (1) Added fatty acid has excellent lubricity and makes tools life longer and finished surface improved.
- (2) The performance to prevent decay contributes to extend the fluid life and to reduce the waste.
- (3) Excellent cleaning property by using materials not aged easily prevents the pollution around machinery.
- (4) Rust of works and tool machineries can be prevented, because stable pH can be kept against the concentration change.
- (5) It is easy to make an emulsion regardless of the temperature or the hardness of water, because this product has excellent self-emulsification ability.

Typical Specifications	Test Item	Test Method	EX Stock Solution	EW(5%)	EW(2%)
	Density at 15°C(g/cm³)	ASTM D4052	0.948	-	-
	Color	ASTM D1500	L1.5	-	-
	Boron(ppm)	ASTM D4951	1>	-	-
	Phosphorus(ppm)	ASTM D4951	1>	-	-
	рН	ASTM D1293	-	9.4	-

**Attention** 

Emulsification can be prepared by adding undiluted solution of DAPHNE ALPHA COOL EW to water. Allowed dilution power is between 2% and 10%.

**Package** 

200L D/M,20L P/L



- Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or via the internet. https://www.idemitsu.com/jp/business/lube/
- Due to continual product research and development, the information contained herein is subject to change without notification.

Malaysia Idemitsu Lube (Malaysia) Sdn. Bhd.

**Kuala Lumpur Branch** Tel: (60) 3 6157 9529 Fax: +60 3 6157 9636 **Johor Branch** 

Tel: (60) 7 550 0460 Fax: +60 7 550 0466 **Penang Branch** 

Tel: (60) 4 501 2268 Fax: +60 4 501 2269

Singapore Branch

Tel: (65) 6256 6843 Fax: +65 6256 6384

Thailand Apollo (Thailand) Co., Ltd Tel: (66) 3 845 6900 Fax: (66) 3 821 0099

Idemitsu Lube Vietnam Co., Ltd.
Tel: (84) 31 3246 508 Fax: (84) 31 3246 509

India

Idemitsu Lube India Pvt. Ltd. Tel: (91) 11 66794200 Fax: (91) 11 66794259 Indonesia PT. Idemitsu Lube Techno Indonesia PT. Idemitsu Lube Indonesia Tel:(62) 21 8997 7630

Philippines Idemitsu Lubricants Philippines Inc. Tel: (63) 2 8 282 855 Fax: (63) 2 8 524 0617