

DAPHNE

Cut HL-5

Description

Daphne Cut HL-5 is applied for the honing and lapping process.

Features & Characteristics

- (1) Active sulfur-type extra low viscosity grinding oil, prolong the life of Grinding wheel and surface accuracy.
- (2) the use of selected Additives assures better penetration and cleaning ability, which leads to the achievement of higher productivity.

Chemical and Physical Properties

Test Item	Test Method	Unit	Result
Density at 15°C	ASTM D4052	g/cm ³	0.868
Flash Point (C.O.C)	ASTM D92	°C	146
Viscosity at 40°C	ASTM D445	mm ² /s	5.0
Copper Corrosion 100°C×1H	ASTM D130	-	3
Sulfur	ASTM D6443	wt%	0.1

Package

200L D/M, 20L P/L

- B Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provide in the Safety Data Sheet (SDS) are followed.
- SDS is available upon request through your sales contract office, or via the internet.
<https://www.idemitsu.com/jp/business/lube/>
- Due to continual product research and development, the information contained herein is subject to change without notification.

Malaysia
Idemitsu Lube (Malaysia) Sdn. Bhd.

Kuala Lumpur Branch
Tel: (60) 3 6157 9529 Fax: +60 3 6157 9636

Johor Branch
Tel: (60) 7 550 0460 Fax: +60 7 550 0466

Penang Branch
Tel: (60) 4 501 2268 Fax: +60 4 501 2269

Singapore Branch
Tel: (65) 6256 6843 Fax: +65 6256 6384

Thailand
Apollo (Thailand) Co., Ltd
Tel: (66) 3 845 6900 Fax: (66) 3 821 0099

Vietnam
Idemitsu Lube Vietnam Co., Ltd.
Tel: (84) 31 3246 508 Fax: (84) 31 3246 509

India
Idemitsu Lube India Pvt. Ltd.
Tel: (91) 11 66794200 Fax: (91) 11 66794259

Indonesia
PT. Idemitsu Lube Techno Indonesia
PT. Idemitsu Lube Indonesia
Tel:(62) 21 8997 7630

Philippines
Idemitsu Lubricants Philippines Inc.
Tel: (63) 2 8 282 855 Fax: (63) 2 8 524 0617