

Product Data Sheet

Idemitsu CVTF

Description

Idemitsu CVTF is the latest advanced continuous variable transmission fluid suitable for use in all modern CVT units. This special formulation consists of high quality hydro cracked base stock and various additives to enhance smooth & positive shifting under severe working conditions.

Application

Recommended for all modern continuous variable transmission gearbox, especially Japanese cars

Characteristics

- Super long-life continuously variable transmission fluid.
- Superior protection against premature wear & tear of moving parts.
- Excellent protection and performance at high temperatures and high loads.

Compatible with:

Amix CVT Fluid-DC, CVT Fluid TC / FE, CVT Fluid NS-1 / NS-2 / NS-3, CVTF 3320, Dia-Queen CVTF J1 / J4, ECVT Fluid / i-CVT Fluid / i-CVT Fluid FG, SCVT Fluid / CVT Fluid Green-1 / Green IV / Green 2, Matic Fluid D

Packing

24 x 1 Litre Carton

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Product Data Sheet

Typical Specifications

Idemitsu CVTF

	ASTM METHOD	
Color (Appearance)		Green
Density 15 °C g/cm ³	D-4052	0.8519
Flash Point (COC) °C	D-92	200
Viscosity, cSt @ 40 °C	D-445	31.10
@ 100 °C	D-445	6.950
BF Viscosity, mPa-s @ -40 °C	D-2983	12,760
Viscosity Index	D-2270	196
Pour Point °C	D-6749	-44.0
TAN,(mgKOH/g)	D-664	1.13
Foaming @ 93.5 °C	D-892	20-0

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.