

Idemitsu IRG3 2T FC

Description

Idemitsu IRG3 2T FC is formulated with high dimensional engine protection and fuel economy. Above international standard and OEM standard.
Semi Synthetic Motor Oil.

Application

For all 2T requiring JASO FC

Characteristics

- Excellent anti-wear protection
- Detergency at high temperatures

Meets or exceeds the performance level of JASO FC

Packing

0.7 Liter

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.

Product Data Sheet

Typical Specifications

Idemitsu IRG3 2T FC

Color (Appearance)	D-1500	Red
Flash Point (COC) °C	D-92	128
Viscosity, cSt @ 40 °C	D-445	51.39
@ 100 °C	D-445	8.139
Pour Point °C	D-97	-
Viscosity Index	D-2270	130
TBN, HClO ₄ (mgKOH/g)	D-2896	9.11
Noack Test 250 °C, 1Hr @ wt%	D5800	-

The information provided is to our best knowledge, true & accurate, subjected to change without notification due to continual product research and development. All recommendations or suggestions are without guarantee since the conditions of use are beyond our control. The manufacturers do not accept liability for any loss or damage, however arising, which results directly from the use of such information, nor do we offer any warranty of immunity against patent infringement.